



IHC1950A

1930 MHz – 1980 MHz HYBRID COUPLER, 90 DGREE, 10 W

REV A
March 2014

Key Features



- Wide Band, 1930 MHz ~ 1980 MHz
- Low Insertion Loss, 0.25 dB Typ.
- High Isolation, 20 dB min
- Excellent VSWR 1.22:1 Typ.
- 90 Degree Hybrid, SMA Connector
- Build-in DC Block Capacitors
- Precision Machined Housing
- Meet MIL-STD-202g

Applications

- Balance Wide Band Power Amplifier
- PCS, 3G
- RF Bench Tests
- Wireless Applications



Absolute Maximum Ratings

Parameters	Units	Ratings
Input Power(at Port 1) CW	W	10
Storage Temperature	°C	-40 ~ +85
Operating Temperature	°C	-40 ~ +85


Operation of this device beyond any one of these parameters may cause permanent damage.

Specifications


Summary of the key electrical specifications at 25°C

Index	Testing Item	Symbol	Test Constraints	Min	Typ	Max	Unit
1	Frequency Range	BW	50 Ohm Impedance	1930		1980	MHz
2	Insertion Loss	S_{21}	1930 – 1980 MHz, above 3 dB		0.25	0.5	dB
3	VSWR	SWR_i	1930 – 1980 MHz, all Ports		1.22:1	1.5:1	Ratio
4	Isolation	S_{23}	1930 – 1980 MHz, 50 Ohm Load at Port C	20	23		dB
5	Amplitude Unbalance	$S_{21} - S_{31}$	1930 – 1980 MHz			1.0	dB
6	Phase Offset	$S_{21} - S_{31}$	1930 – 1980 MHz	87	90	93	Deg
7	Power Handling	P_{MAX}	1930 – 1980 MHz, CW			10	W
8	Operating Temperature	T_o		-40		+85	°C

Functional Block Diagram



Outline, IP-1 Housing







Ordering Information

Model Number	Connectors	
	IN	OUT
IHC1950A	SMA Female	SMA Female

Specifications and information are subject to change without notice.



Typical Data



Application Notes:

A. SMA Torque Wrench Selection

Always use a torque wrench with 5 ~ 6 inch-lb coupling torque setting for mating the SMA cables to the amplifier. Never use torque more than 8 inch-lb wrench for tightening the mating cable to the connector. Otherwise, the permanent damage will occur to the SMA connectors of the amplifier. 8710-1582 (5 inch-lb) is one of the ideal torque wrench choice from Agilent Technology.

B. Mounting the Amplifier

Use three pieces of #2-56 with longer than 9/16" screws for mounting the amplifier on a metal-based chase. Flat and spring washers are needed to prevent the screw loosening during the shock and vibration. Always use the appropriate torque setting of the power screwdriver to mount them.

Specifications and information are subject to change without notice.